

Product Name

H1

(Tm Driver)

Technical description

Suspension fitting which stands out by its characteristic cleanliness and elegance, H1 intends to bring together the most advanced technology solutions in a classic and traditional style. Thanks to these peculiarities, H1 finds its ideal habitat in the most varied applications; In fact, it can be installed in shops, exhibitions, commercial areas or industrial environments. Body in die cast aluminum alloy UNI EN 1706 polyester powder coated with aluminum reflector turned, anodized and polished. Stainless steel screws AISI 304. LED light source (lumileds), colour temperature (4000 K Neutral White). High coefficient of performance chromatic CRI>80.



Supply

External driver (available in dimmable or DALI versions)
Voltage 220 - 240 V AC 50/60 Hz.
Temperature -40° +45°

Installation

Suspended.

Applications

Commercial areas and industrial areas of small/medium size.

Size (mm)



Ø 325 x 320

Colour

Aluminium 6

Decay of the luminous flux

≥100.000 hr L85B15



Code	Source	Power	Lm (Output)	Lm (Tc=25°)	Temperature	CRI	Beams	Colour
L00H14080BL60060	LED	60 W	6394 lm	10260 lm	4000 K	≥80	80°	Aluminium

Accessories



Fast connector
IP 3 poles
LKITA00000000003



Cable with
connector
LKITA00000000040
LKITA00000000041

Lanzini indicates the luminous flux of the luminaire in the catalogs with a tolerance of ± 10% respect to the indicated value. The total W indicates the total power absorbed by the LED + power supply system that does not exceed 10% of the indicated value.