

# Slice M

## L12 115A7 \_

### Technical description

Adjustable LED fitting for wall use and/or with stake, complete with bracket, extremely robust, with high IP protection, suitable for soft pointing lighting for indoor and outdoor use. This fitting is equipped with integrated LED modules.

Die-cast aluminium body, complete with lid and soft lens optic, screws in stainless steel AISI 304. Gasket in silicone rubber that provides a high resistance to water splashes. Powder paint with high resistance to external agents.

LED light source COB and colour temperature (2700K).

Very high coefficient of rendering >80CRI.

### Supply

Driver included.

Input voltage 220-240 VAC/50-60Hz

Temperature -20° +40°

Life 25000h / 25°

### Installation

Spot for outdoor



### Size (mm)

112 x 106 x 145

### Color

White  1 Grey  2 Dark Grey  4

  IP65



Code	Source	Power	Luminous Flux	Temperature	CRI	Beams	Color
L12 115A7 1	LED COB	9 W	900 lm	2700 K	>80	30°	White
L12 115A7 2	LED COB	9 W	900 lm	2700 K	>80	30°	Grey
L12 115A7 4	LED COB	9 W	900 lm	2700 K	>80	30°	Dark Grey

### Accessories



Stake  
L92 011000



Fast connector IP  
L93 043000