

Slice L

L12 202A7 _

Technical description

Adjustable LED fitting for wall use and/or with stake, complete with bracket, extremely robust, with high IP protection, suitable for soft pointing lighting for indoor and outdoor use. This fitting is equipped with integrated LED modules.
Die-cast aluminium body, complete with lid and soft lens optic, screws in stainless steel AISI 304. Gasket in silicone rubber that provides a high resistance to water splashes. Powder paint with high resistance to external agents.
LED light source COB and colour temperature (3000K).
Very high coefficient of rendering >80CRI.

Supply

Driver included.
Input voltage 220-240 VAC/50-60Hz
Temperature -20° +40°
Life 25000h / 25°

Installation

Spot for outdoor

Size (mm)


133 x 124 x 157

Color

White 1 Grey 2 Dark Grey 4

  IP65

Code	Source	Power	Luminous Flux	Temperature	CRI	Beams	Color
L12 202A7 1	LED COB	15 W	1200 lm	3000 K	>80	30°	White
L12 202A7 2	LED COB	15 W	1200 lm	3000 K	>80	30°	Grey
L12 202A7 4	LED COB	15 W	1200 lm	3000 K	>80	30°	Dark Grey



Accessories



Stake
L92 011000



Fast connector IP
L93 043000