

# Standard track 1 m

## L93 00100 \_

### Technical description

Body in extruded aluminium, internally accommodates conductors encased PVC extruded in high-resistivity insulation IP20.  
Tri-phase rail (L1, L2, L3), neutral (N), grounding (PE). The track can support a load of 2 kg every 200 mm with a maximum distance between the fastening points of 800mm.

### Supply

16A Class I  
EN 60570  
230-400 V AC/50-60 Hz

### Installation

Ceiling / Hanging


### Size (mm)

1000 x 36 x 33

### Colour


White  1 Grey  2 Black  3

  IP20



Code	Size	Colour
L93 00100 1	1000 mm	White
L93 00100 2	1000 mm	Grey
L93 00100 3	1000 mm	Black

### Accessories



Right power supply head  
Cod. L93 00700 \_  
Left power supply head  
Cod. L93 00900 \_



90° joint curve - internal  
Cod. L93 02400 \_  
90° joint curve - external  
Cod. L93 02500 \_




Linear joint  
Cod. L93 02000 \_




Closing top  
Cod. L93 00600 \_



Flexible joint  
Cod. L93 02600 \_




4-ways joint  
Cod. L93 02800 \_



Mechanical joint  
Cod. L93 00500 0



3-way joint  
Cod. L93 02700 \_




Adjustable joint  
Cod. L93 04100 \_



Ceiling kit  
Cod. L93 01900 0



Hanging kit  
Cod. L93 01500 \_



Hanging kit  
Cod. L93 01600 \_



Ceiling mounting kit  
Cod. L93 01800 0



Retractable linear joint CC  
Cod. L93 02200 \_  
Retractable linear joint SC  
Cod. L93 02300 \_