

Standard track 3 m

L93 00300 _

Technical description

Body in extruded aluminium, internally accommodates conductors encased PVC extruded in high-resistivity insulation IP20.
Tri-phase rail (L1, L2, L3), neutral (N), grounding (PE). The track can support a load of 2 kg every 200 mm with a maximum distance between the fastening points of 800mm.

Supply

16A Class I
EN 60570
230-400 V AC/50-60 Hz

Installation

Ceiling / Hanging


Size (mm)

3000 x 36 x 33

Colour


White 1 Grey 2 Black 3

  IP20



Code	Size	Colour
L93 00300 1	3000 mm	White
L93 00300 2	3000 mm	Grey
L93 00300 3	3000 mm	Black

Accessories



Right power supply head
Cod. L93 00700 _
Left power supply head
Cod. L93 00900 _



90° joint curve - internal
Cod. L93 02400 _
90° joint curve - external
Cod. L93 02500 _




Linear joint
Cod. L93 02000 _




Closing top
Cod. L93 00600 _




Flexible joint
Cod. L93 02600 _




4-ways joint
Cod. L93 02800 _



Mechanical joint
Cod. L93 00500 0



3-way joint
Cod. L93 02700 _




Adjustable joint
Cod. L93 04100 _



Ceiling kit
Cod. L93 01900 0



Hanging kit
Cod. L93 01500 _



Hanging kit
Cod. L93 01600 _



Ceiling mounting kit
Cod. L93 01800 0



Retractable linear joint CC
Cod. L93 02200 _
Retractable linear joint SC
Cod. L93 02300 _