

Product Name

**L2**

(1800 mm)

Technical description

LED fitting in extruded aluminum square section, direct mono emission, continuous form without structural interruptions, suitable in pendant version, ceiling, wall and recessed no frame. Polycarbonate diffuser with high luminous efficiency. Body in die-cast aluminium according to the regulations UNI 5076 EN - AB 46100. Diffuser made of prismatic technopolymer LED light source and colour temperature ( 4000 K Neutral White ). Very high coefficient of rendering  $\geq 90$ CRI. Glare value UGR < 19

Supply

Driver included.  
Input voltage 220-240 V AC/50-60Hz  
Temperature -20° +40°  
Life 30000h / 25°

Installation



Suspension, ceiling, wall and recessed no frame.

Size (mm)

1800 x 51 x 75

Colour

White aluminium 6



Code	Source	Power	Luminous Flux	Temperature	CRI	Beams	Colour	Control
L00L24000D160045	LED	45 W	3825 lm	4000 K	$\geq 90$	UGR <19	Aluminium	Dimmer

Accessories



Wall mounting kit  
LKITA00000000030



Ceiling kit  
LKITA00000000031



No frame recessed kit  
LKITA00000000032



Hanging kit  
LKITA00000000033



Power kit  
LKITA00000000034