

Optical Big

LB3 205A3 _

Technical description

LED fitting for tri-phase track. Body in die cast aluminium and anodized aluminium reflector with high luminous efficiency. This fitting is equipped with integrated LED modules. Body in die-cast aluminium according to the regulations UNI 5076 EN - AB 46100. Optics in polycarbonate. LED light source CREE COB and colour temperature (3000 K). Very high coefficient of rendering >90CRI.

Supply

Driver included.
 Input voltage 220-240 V AC/50-60Hz
 Temperature -20° +40°
 Life 30000h / 25°

Installation



Tri-phase track

Size (mm)

145 x 95 x 145

Colour

White 1 Grey 2 Black 3



| Code | Source | Power | Luminous Flux | Temperature | CRI | Beams | Colour |
|-------------|----------|-------|---------------|-------------|-----|-------|--------|
| LB3 205A3 1 | COB CREE | 35 W | 2508 lm | 3000 K | >90 | 15° | White |
| LB3 205A3 2 | COB CREE | 35 W | 2508 lm | 3000 K | >90 | 15° | Grey |
| LB3 205A3 3 | COB CREE | 35 W | 2508 lm | 3000 K | >90 | 15° | Black |


Accessories



Barndoors
LKITA00000030019



Anti-glare screen
LKITA00000030021



Honeycomb louvre
LKITA00000030020